



Service Manual

Multi Compact Disc Player

CP-M405 (GERMANY)
(EUROPE)



Specifications

PRODUCT CODE No.
137 059 00 Germany
137 059 01 Europe (MSM)

Note :

The below mentioned specifications are mainly based on the IHF measurements standard. They can therefore not directly be compared with specifications based on the DIN standard or other standards.

CD player

Channels	2-channel
Frequency response	20 - 20,000 Hz
Signal to noise ratio	102 dB
Channel separation	94 dB (1 kHz)
Distortion	0.05% (1 kHz)
Wow and flutter	Undetectable
Outputs	1.8V / 1k ohms

Signal format

Sampling frequency	44.1 kHz
Quantization	16 bits linear/channel
Transmission rate	4.32 Mbit/sec.

Pickup

System	Light pickup (3 - beam)
Light source	Semiconductor laser
Wave length	790 nm

General

Power supply	AC : 230V, 50HZ
Dimensions(approx.)	420 (W) x 115 (H) x 370 (D) mm

Remote controller (RB-M405)

Note: The POWER switch is mounted on the secondary side, The unit is not disconnected from AC power, even when switched off.

Specification subject to change without notice.

REFERENCE No. WM-580705

SCHEMATIC DIAGRAM (CD)



