

DUROLYT

	A	B	C
1			
2		Hans M. Knoll 08. 2013	
3		Messen von Kondensatoren aus SABA-Radios	24.08.2013
4		Muster Th. Ki.	Wertaufdruck
5	Muster 1	WIMA DUROLYT 1000V= 400V~ (b) VDE Zeichen 0560-2	4700 (pF)
6	Muster 2	WIMA DUROLYT 1000V= 400V~ (b) VDE Zeichen 0560-2	4700 (pF)
7	Muster 3	WIMA DUROLYT 400V= hat Risse	0,01 (uF)
8	Muster 4	WIMA DUROLYT 400V=	0,01 (uF)
9	Muster 5	ERO KT1801 630V= 200V~ +/- 10%	4700 (pF)
10	Muster 6		
11	Muster 7		
12	Muster 8		
13	Muster 9		
14	Muster 10		
15	Muster 11		
16	Muster 12		
17	Muster 13		
18	Muster 14		
19	Muster 15		
20	Muster 16		
21	Muster 17		
22	Muster 18		
23	Muster 19		
24	Muster 20		
25	Wert #1	Isolation mit 250V= COMARK Electronics LTD. GBr	
26	Wert #2	Kapazität mit R&S LARU	
27	Wert #3	Kapazität mit PHILIPS GM4414	
28	Wert #4	Kapazität mit MARCONI Univ. Bridge TF2700	
29	Wert #5		
30	Wert #6		

DUROLYT

	D	E	F	G	H	I	J	K
1								
2								
3	COMARK	LARU	LARU	PHILIPS	PHILIPS	MARCONI	MARCONI	
4	Wert #1	Wert #2	Q-Wert	Wert #3	Q-Wert	Wert #4	Q-Wert	
5	1,56 Gohm	6800 pF	low	6900 pF	mittel	6940 pF	1,5 x 0,01	
6	1,56 Gohm	6400 pF	low	6500 pF	gut	6600 pF	1,4 x 0,01	
7	10 Meg	15nF	low	29 nF	down	17 nF	0,3	
8	160 Meg	14nF	low	15,5 nF	low	14,8 nF	0,24 x 0,01	
9	5,0 Gohm	4600pF	low	4520	high	4680 pF	0,3x 0,01	
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								